



Norsat
International Inc.



Innovative Communication Solutions

CFK-4200 Compact Flyaway Kit

The Norsat CFK-4200 Emergency Communications Kit gives first responders the capability to connect to remote resources while in the field under adverse circumstances. To maximize flexibility, the system provides users with the ability to establish reliable communications via three methods: BGAN satellite, satellite phone, or a cellular data network (EV-DO or UMTS).

The Emergency Communications Kit also acts as a mobile office with an integrated scanner, printer, HD webcam, and rugged laptop. With the key components already connected, setup of the system is easy.

The 4200V is an enhanced multimedia version of the kit. It adds a video camera, video editing software, support accessories, and an additional transit case.

Key Features

The Norsat CFK kits are high performance integrated fly-away kits packaged in two airline carry-on cases, these kits provide secure and non-secure communications via an ethernet connection. Key features include:

- Ruggedized Laptop
- BGAN Satellite terminal
- Wireless cellular data modem
- Integrated printer and scanner
- Compact Pelican case
- High Definition USB webcam
- Diverse powering: AC or DC
- 4200V variant adds support for video capture and editing

Norsat Global Customer Support

All CFK kits are supported by Norsat's global customer support team, who provide assistance for a range of technical issues. Customer support may include installation, training, trouble-shooting, application support, and 24/7/365 support is available to support mission critical applications.



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+336 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com

NORSAT CFK-4200 EMERGENCY COMMUNICATIONS KIT

INCLUDED ACCESSORIES

- 7 Port USB Hub
- 2.0 Megapixel webcam
- USB Mouse
- USB-Powered light
- VoIP Software

DETAILED SPECIFICATIONS


- Dimensions: 22" L x 18" W x 10.5" H
- Weight: 57 lbs
- Power input: 100-130 wVAC 60Hz, 11-32 VDC
- Operating temperature: 32° to 149° F (-20° to 65° C)
- Storage Temperature: 4° to 149° F (-20° to 65° C)
- Humidity: 5 to 95%, non- condensing

SAT PHONE OPTIONS

- Globalstar, Iridium, Thuraya or Inmarsat

4200V AUDIO/VIDEO OPTION

- Firewire hub
- Video encoder and audio codec
- Video camera and video editing software
- Microphone and headphones
- Additional transit case



Connectivity	Typical Speeds	Standard or Optional	Voice	Data	Video
Inmarsat BGAN w/Analog phone	128-256 kbps	Standard	✓	✓	
Iridium or Globalstar or Inmarsat Satphone	Voice/kbps	Optional	✓		
Cellular (EV-DO or UMTS)	1-2 Mbps	Optional	✓	✓	✓
Local LMR Interoperability	Voice	Optional	✓		
Microsat (X, Ku, Ka)	3-5 Mbps	Optional	✓	✓	✓
Secure Meshing Wi-Fi	54 Mbps	Optional	✓	✓	✓

Specifications subject to change



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+336 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com