

Advanced MIMO OFDM Radio

CableFree Pearl Low Cost Integrated Client Radio

Overview



About Wireless Excellence

Founded in 1996 and with headquarters in Oxford UK, Wireless Excellence Limited is a leading designer and supplier of outdoor and indoor Broadband Wireless communication products.

With a complete range of solutions including Radio, Microwave, Millimeter-Wave, Free Space Optics, WiFi and 4G/5G/LTE, customers in over 80 countries have chosen Wireless Excellence as the “one stop shop” solution of choice for dependable wireless networking.

About Our OFDM Range

CableFree OFDM Radio solutions deliver the performance, reliable connectivity, and cost-effectiveness that are crucial to modern wireless broadband networks. Our scalable wireless platform delivers superior performance even in demanding conditions, with the flexibility and features to enable a wide range of applications. CableFree OFDM Radio technology combines the best hardware and software technology to ensure best possible network performance.

System Features

- Advanced MIMO OFDM Radio Platform
- Ideal Low Cost CPE for P2MP deployment or P2P link
- Raw data rates up to 867Mbps (AC) or 300Mbps (N version) using 2x2 MIMO OFDM
- 5.1-5.8GHz ISM bands
- Supports extended 4.9-6.0GHz licensed bands
- Range up to 15km*
- DFS and TPC features for regulatory regional compliance
- Data Throughput up to 530-650Mbps (AC) or 250Mbps (N version)
- Carrier-class OS and resiliency features
- Power-over-Ethernet technology
- Rugged environmental IP55 enclosure
- 200Km/h Wind Resistance
- Near & Non- LOS Operation
- 2 x 2 MIMO Support
- Interface Options include 1x 10/100 Port (1 x GigE on AC version)**
- Modulation up to 256QAM (AC) or 64QAM (N version)

*Depends on radio environment

Embedded Router Platform

CableFree OFDM radios from Wireless Excellence are high-performance carrier-grade Radio Solutions. They embody state-of-the-art software-defined-radio hardware, coupled with a powerful carrier-class router operating software with advanced Layer 2 Bridging and Layer 3 Routing features:

- High performance CPU, 720MHz (AC) 400MHz (N Version) MIPS architecture; AC
- IP Bridging
- Layer3 IP Routing
- Advanced Networking: RSTP, BGP, OSPF & MPLS
- VPN and Ethernet-over-IP (EoIP) tunnels
- Virtual Router Redundancy Protocol (VRRP)
- WISP & hotspot –specific features including Walled Garden, Cookies, RADIUS authentication, accounting, control of connection time
- Advanced, feature-rich QoS & traffic prioritisation
- Uplink and downlink bandwidth control on a per-user basis
- Firewall, NAT, DHCP Client and Server

Enhanced Wireless Performance

CableFree OFDM radios from Wireless Excellence offer major advantages over competing radio products. Examples are:

- Highly configurable
- 867Mbps or 300Mbps raw data rate using 2x2 MIMO features offers up to 650 or 250Mbps throughput
- OFDM Software-defined radio – ‘state-of-the art’ radio using powerful DSP technology
- Software Selectable 5, 10, 20, 40, 80MHz; also custom channel widths available
- Optional proprietary streaming wireless protocols - improve P2P and P2MP wireless links through packet optimisation. No protocol/speed degradation for long links. Added security layer. Full duplex option using dual wireless cards
- Sophisticated RadioOS software platform
- Hotspot features including Radius authentication and per-user bandwidth controls

Applications

- Point-to-Point or Point-to-Multipoint Data network segments
- Wireless ISP or Hotspots
- Resilience for FSO or Fibre links
- Fast Roll-out & Temporary Deployment



Specifications

System Variant	CF-Pearl-LC-XXX
Performance	
Range	Up to 15km, depending on antenna options, P2P or P2MP deployment
Bandwidth	bandwidth up to 250Mbps (300Mbps raw speed) in 2x2 MIMO mode Antenna; AC Version, bandwidth up to 530-650Mbps (867Mbps raw speed) with AC 2x2 MIMO mode
Power Consumption	10W; 12 - 48V fed from Power-over-Ethernet injector (Factory Option); 115/230Vac; optional Uninterruptible Power Supply (UPS)
Operating Temp	-40...+60 deg C
Wireless	
Frequency	5GHz: 5.150-5.350 (5 MHz step) 5.725-5.825 (5 MHz step) 5.47-5.725 GHz, 4.90-6.00GHz DFS (Dynamic Frequency Select) feature for regions requiring DFS enabled
Radio Type	Direct Sequence Spread Spectrum (DSSS)
Modulation	5GHz: OFDM (BPSK, QPSK, 16-QAM, 64-QAM); Dynamic (Adaptable to Conditions)
RF Channels	Software Selectable 5, 10, 20, 40MHz; also custom channel widths available; AC version up to 80MHz
Latency	<3ms
RF Output Power	18dBm (63mW, standard power) or 28dBm (630mW, high power version)– TPC (Transmit Power Control), 1dB steps under software control. Minimum power 0dBm
Sensitivity @FER=0.08:	54 Mbps OFDM -73 dBm; 48 Mbps OFDM -76 dBm; 36 Mbps OFDM -82 dBm; 24 Mbps OFDM -85 dBm; 18 Mbps OFDM -88 dBm; 12 Mbps OFDM -89 dBm; 11 Mbps OFDM -91 dBm; 9 Mbps OFDM -90 dBm; 6 Mbps OFDM -91 dBm; 5.5Mbps OFDM -92 dBm; 2 Mbps OFDM -93 dBm; 1 Mbps OFDM -94 dBm
Radio Data Rate	2GHz & 5GHz (Normal mode): 300, 270, 240, 180, 120, 90, 60, 30, 150, 135, 120, 90, 60, 45, 30, 15, 108, 96, 72 48, 36, 24, 18, 12 Mbps, 54, 48, 36, 24, 18, 12, 9, 6 Mbps, auto-fallback
Compatibility	Proprietary modes plus back compatibility fully interoperable with IEEE 802.11a/b/g compliant products
Radio Architecture	Support ad-hoc, peer-to-peer networks and infrastructure communication to wired Ethernet networks via Access Point
Security	64/128-bit WEP data encryption; WPA, WPA2, TKIP, CCMP, AES; Proprietary modes
Antenna	
Type	Integrated Directional, Flat Panel, Dual Polarised
Gain	19dBi
Router Platform	
CPU	MIPS 400MHz or 720MHz; 128MB SRAM; 1GB FLASH memory
System Software Management	RadioOS 8.1; Choice of license levels 1-6; Remotely Upgradeable via TFTP
Resilience Features	Local and Remote configuration, control and administration via RS232, Telnet, HTTP, SNMP and Proprietary protocols
	Virtual Router Redundancy Protocol (VRRP) allows two complete radio ODUs to be configured with one in 'hot standby' for high-availability applications
Mechanical	
Dimensions (mm)	386x386x70mm
Connectors	External: 10/100/1000 Ethernet: RJ45
Environmental	IP55
Weight	2kg

Part Numbers

Product Code	Description
CF-Pearl-LC-5G-N-U-19	Pearl LC Unit, 4.9-6.0GHz, Single Unit, 300Mbps, 10/100/1000 Interface, integrated 19dBi antenna
CF-Pearl-LC-5G-N-B-19	P2P Pearl LC Link, 4.9-6.0GHz, Single Unit, 300Mbps, 10/100/1000 Interface, integrated 19dBi antenna
CF-Pearl-LC-5G-AC-U-19	Pearl LC Unit, 4.9-6.0GHz, Single Unit, 867Mbps, 10/100/1000 Interface, integrated 19dBi antenna
CF-Pearl-LC-5G-AC-B-19	Pearl LC P2P Bundle, 4.9-6.0GHz, Single Unit, 867Mbps, 10/100/1000 Interface, integrated 19dBi antenna

T: +44 (0)870 495 9169
E: sales@cablefree.net
W: www.cablefree.net

Wireless Excellence Limited
The Oxford Science Park,
G6, Magdalen Centre
Robert Robinson Avenue,
Oxford OX4 4GA

+ note that versions with external antennas can be supplied. Please enquire for more details