

1.2 Meter Prodelin Tx Rx Antenna (Series 1134) – Intelsat



Your Trusted Source for Satellite Equipment



P120KUI

- Intelsat Type Approved
- Precision Compression Molded Reflector
- Universal or Non Penetrating Roof Mount Options Available

Electrical		Series 1134 Ku-Band
Antenna Size		1.2 M (48 in.)
Operating Frequency (GHz)	Receive Transmit	10.95 - 12.75 GHz 14.00 - 14.50 GHz
Midband Gain (+ .2dB)	Receive Transmit	41.50 dBi 43.00 dBi
Antenna Noise Temperature		
20° Elevation		46 K
30° Elevation		43 K
Sidelobe Envelope, Co-Pol (dBi)		
1° ≤ θ ≤ 20°		29 - 25 Logθ dBi
20° < θ < 26.3°		-3.5 dBi
26.3° < θ ≤ 48°		32 - 25 Logθ dBi
48° < θ		-10 dBi (averaged)
Cross-Polarization	Within 1 dB contour Any Angle off Axis	-30 dB Max. -25 dB Max.
VSWR		1.3:1 Max.
Mechanical		
Reflector Material		Glass Fiber Reinforced Polyester SMC
Antenna Optics		Prime Focus, Offset Feed
Mast Pipe Size		2 1/2" SCH 40 Pipe (2.88" OD) 73.2 mm.
Elevation Adjustment Range		5° to 90° Continuous Fine Adjustment
Azimuth Adjustment Range		+/- 20° Fine, 360° Continuous
Mount Type		Elevation over Azimuth
Shipping Specifications		90 lbs. (41 kg.)
Environmental Performance		
Wind Loading	Operational Survival	50 mph (80 km/h) 125 mph (201 km/h)
Temperature	Operational Survival	-40° to 140° F (-40° to 60° C) -50° to 160° F (-46° to 71° C)
Rain	Operational Survival	1/2"/hr 2"/hr
Ice	Operational Survival	----- 1/2" radial
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation		360 BTU/h/ft ²

TX-RX_P120KUI_PR-1134_REV002

Specifications are subject to change without notice

sales@vikingsatcom.com • www.vikingsatcom.com

T: 517.629.3000 • F: 517.629.2379 • 704 North Clark Street • Albion, MI