



- Frequency Range 4.5 - 4.8 GHz
- L.O stability $\pm 5, 10, 25$ KHz max.
- Power supply $\pm 5, 10, 25$ KHz max.
- Power connector Feed thru and/or output connector




Block Downconverter C-Band 4548 (BDC)

Model: GBDC45485, GBDC454810, GBDC454825

Specifications

Parameter	Specification
Input Freq.	4.5 - 4.8 GHz
Output Freq.	1150 – 1450 MHz
L.O Freq.	5.95 GHz
Noise figure	10 dB max
Conversion gain at -40 to +60°C	40 dB typ. (37dB min. 43dB max.)
Gain flatness	4 dBp-p max.
Gain flatness at -40 to +60°C	5 dBp-p max.
Gain ripple at per 27MHz, -30 to +60°C	1 dBp-p max.
L.O stability at -40 to +60°C	$\pm 5, 10, 25$ KHz max.
Image rejection	45 dBc min.
Phase noise	-73 dBc/Hz (@ 1KHz) -83 dBc/Hz (@ 10KHz) -93 dBc/Hz (@ 100KHz)
Output P1dB	+5 dBm min.
Input VSWR	2.0: 1 max
Output VSWR	2.0: 1 max
Input connector	SMA-type female
Output connector	F, N, SMA-type female (option)
Power supply	+12 to +24V DC
Power supply connector	Feed thru and/or output connector
Required current	300 mA max.
Operating temperature	-40 to +60°C
Waterproof	IP 67
Dimension (exclude connector)	108.0 x 94.0 x 46.0 mm
Weight	620 g

Mechanical Diagram (Unit: inch (mm))



www.geosatmicrowave.com

sales@geosatmicrowave.com