



- Compact and energy efficient
- Solid State Reliability
- Easy System Integration
- Thermally Efficient
- Low Thermal Noise
- Frequency agile design covers complete frequency band
- Superior Harmonic and Spurious Suppression
- 3 Year GeoSat Product Warranty

12W Linear Ka-Band Block Up-Converter (BUC)

Model: GB41KAL931



Section	Item	Specification
Power Requirement	Voltage	+48VDC (prime), +28VDC, 90 - 264VAC @50/60 Hz
	Power Consumption	235W Prime Power at 12 W Linear Output Power
RF Characteristics	Frequency	29.0 - 31.0 GHz (single model covers frequency range)
	Psat	20 Watts (Typical)
	Output Power P-Linear	12 Watts
IF Characteristics	Frequency Range	1000-2000 MHz; 950-1450 MHz; 950-1950 MHz
	Impedance	50 Ohms
	Input VSWR	1.5:1 Max
	Input Level	-10 dBm Nominal
Interface:	IF Input	N-Female
	Reference Input	Multiplexed with IF Input
	RF Output	WR 28
	Monitor & Control I/O	RS-485 or Ethernet (SNMP/HTTP)
	Ethernet Connector	Weatherproof RJ-45
	Serial Monitor & Control Connector	Mil-Circ- Bayonet
External Reference:	Power Connector	Mil-Circ- Bayonet
	Frequency	10 MHz
	Frequency Stability	Per Mil-Std-188-115
	Input Level	-10 to +10 dBm

Continued on the next page ▼

Section	Item	Specification		
Transfer Characteristics	Type	Single Conversion		
	Frequency Sense	Non-inversion		
	Gain	55 dB +/-2 dB		
	Gain Flatness @ Maximum Gain ▼	Over RF Output band:	± 2 dB. Max.	
		Over any 125 MHz segment	±0.50 dB Max.	
		Over any 40 MHz segment	±0.3 dB Max.	
	Gain Adjustment Range	30 dB. Min.		
	Mute	-60 dB relative to P-Linear		
	Gain Variation over operational temp	±2.0 dB max.		
	Gain Step Size	0.25 dB max.		
	Group Delay variation	3.5 nsec over 36 MHz Meets Mil-Std 188-164B		
	Third Order IMD @ P-Linear	With two output carriers @ 40.8dBm total output power: -25 dBc referenced to total output power, Max.		
	Output Noise Density TX	-75 dBm/Hz		
	Output Noise Density in RX Band	-157 dBm/Hz		
	Spurious	-60 dBc max.		
	Harmonics	-60 dBc max. measured at P-Linear		
	Spectral Regrowth		-30 dBc at P-Linear, QPSK, 5 Ms/s, Alpha=30% at 1 x symbol rate away from the carrier.	
		Phase Noise ▼	100Hz	-32 dBc/Hz max.
			100Hz	-63 dBc/Hz max.
			1kHz	-72 dBc/Hz max.
			10kHz	-82 dBc/Hz max.
100kHz			-92 dBc/Hz max.	
1mHz			-112 dBc/Hz max.	
10mHz			-122 dBc/Hz max.	
Output VSWR	1.3:1 Max Infinite @ 5 Watts			
Max Load VSWR (no damage)	Infinite @ 12 Watts Linear Output Power			
Environmental:	Operating Temperature Range	-40°C to +60°C		
	Storage Temperature Range	-40°C to + 85°C		
	Humidity	100% Condensing		
	Altitude	10K ft.		
	Vibration	MIL-STD-810G		
	Shock	MIL-STD-810G		
Physical	Size	(LxWxH): 7.8" x6.7" x 5.4"		
	Weight	14 lbs.		
	FAN	Field Replaceable		