



- *Min. 38dBm Output P1dB over Temp.*
- *Light Weight & Small Size*
- *Leak Protected and 100% Screened*
- *RoHS Compliant*
- *3 Year GeoSat Product Warranty*

6W Ku-Band Block Up-Converter (BUC)

Model: GB38SKU1N



Section	Item	Specification		
Power Requirement	Voltage	+15 ~ +24V DC		
	Power Consumption	48W max		
Input Characteristics	Frequency Range	950 ~ 1450MHz		
	Impedance	75 / 50 Ohms		
	Gain at Compression Point	53dB min		
	IF Connector	F / N-Type (Female)		
Output Characteristics	Frequency Range	14.0 ~ 14.5GHz		
	Power @ 1dB Comp.	Min. 38dBm over temp.		
	Gain Flatness (500 MHz)	5dB p-p max		
	RF Connector	WR 75		
Transfer Characteristics	Frequency Sense	Non Inverted		
	Local Frequency	13.05 GHz		
	External Reference Frequency	10MHz, Sine wave		
	Gain	55 dB typ. @ 25 °C		
	Phase Noise ▼	Reference Phase Noise @ -/+ 5dBm Input		
		100Hz	< -60dBc / Hz	< -135dBc / Hz
		1kHz	< -70dBc / Hz	< -140dBc / Hz
10kHz		< -80dBc / Hz	< -143dBc / Hz	
100kHz	< -90dBc / Hz	< -148dBc / Hz		
Mute	HPA is turned off in case of LO unlocked.			
Mechanical	Dimension (mm)	189 x 184 x 74mm		
	Weight	2.3kg		
	Painting	White Color		
Operating Temperature	- 40°C ~ + 55°C			