



- Frequency Range 4.5 - 4.8 GHz
- Power supply +12 to +24V DC
- Power connector MS3112E10-6P (option)



## Low Noise Amplifiers C-Band 4548 (LNA)

Model: GLAC4548

### Specifications

Parameter	Specification
Frequency range	4.5 – 4.8
Noise temperature	30°K max.
Conversion gain at -40 to +60°C	55dB typ. (50dB min. 60dB max.)
Gain flatness	4 dBp-p max.
Gain flatness at -40 to +60°C	4 dBp-p max.
Gain ripple at per 27MHz, -40 to +60°C	1 dBp-p max.
Output P1dB	+5 dBm min.
Input VSWR	2.2 : 1 max
Output VSWR	2.2 : 1 max
Input waveguide flange	WR-229
Output connector	N, SMA type female (option)
Power connector	MS3112E10-6P (option)
Power supply	+12 to +24V DC
Required current	150 mA max.
Operating temperature	-40 to +60°C
Waterproof	IP 67.
Dimension (exclude connector)	98.8 x 70.0 x 164.5 mm
Weight	630 g

[www.geosatmicrowave.com](http://www.geosatmicrowave.com)

[sales@geosatmicrowave.com](mailto:sales@geosatmicrowave.com)

# Mechanical Diagram (Unit: inch (mm))

