



- Frequency Range 17.2 - 18.2 GHz
- Power supply +12 to +24V DC
- Power connector MS3112E10-6P (option)



Low Noise Amplifiers Ka-Band 1718 (LNA)

Model: GLAKA1718


Specifications

Parameter	Specification
Frequency range	17.2 - 18.2 GHz
Noise figure	1.5 dB max.
Conversion gain at -40 to +60°C	55dB typ. (50dB min. 60dB max.)
Gain flatness	4 dBp-p max.
Gain flatness at -40 to +60°C	5 dBp-p max.
Gain ripple at per 27MHz, -40 to +60°C	1 dBp-p max.
Output P1dB	+5 dBm min.
Input VSWR	2.2 : 1 max
Output VSWR	2.2 : 1 max
Input waveguide flange	WR-42
Output connector	N, SMA type female (option)
Power connector	MS3112E10-6P (option)
Power supply	+12 to +24V DC
Required current	250 mA max.
Operating temperature	-40 to +60°C
Waterproof	IP 67.
Dimension (exclude connector)	60.0 x 45.0 x 111.5 mm
Weight	450 g

www.geosatmicrowave.com

sales@geosatmicrowave.com

Mechanical Diagram (Unit: inch (mm))



www.geosatmicrowave.com

sales@geosatmicrowave.com