



- 4 bands are switchable
- Frequency Range 17.2- 22.2GHz
- Built-in Isolator
- 10KHz stability



Low Noise Block Ka-Band 4 LO PLL with W/G Isolator (LNB)

Model: GLKAB4LOI

	Section	Item	Specification
GLKAB4LOI (1)	Band 1	Input (GHz)	17.20 - 18.20
		Output (MHz)	950 - 1950
		L.O (GHz), Switching	16.25 @13V
	Band 2	Input (GHz)	18.20 - 19.20
		Output (MHz)	950 - 1950
		L.O (GHz), Switching	17.25 @13V & 22KHz
	Band 3	Input (GHz)	19.20 - 20.20
		Output (MHz)	950 - 1950
		L.O (GHz), Switching	18.25 @18V
Band 4	Input (GHz)	20.20 - 21.20	
	Output (MHz)	950 - 1950	
	L.O (GHz), Switching	19.25 @18V & 22KHz	
GLKAB4LOI (2)	Band 1	Input (GHz)	18.20 - 19.20
		Output (MHz)	950 - 1950
		L.O (GHz), Switching	17.25 @13V
	Band 2	Input (GHz)	19.20 - 20.20
		Output (MHz)	950 - 1950
		L.O (GHz), Switching	18.25 @18V
	Band 3	Input (GHz)	20.20 - 21.20
		Output (MHz)	950 - 1950
		L.O (GHz), Switching	19.25 @18V & 22KHz
	Band 4	Input (GHz)	21.20 - 22.20
		Output (MHz)	950 - 1950

