

This versatile receive filter rejects the extended (INSAT) transmit band (6.725 - 7.025 GHz), and <u>also rejects</u> transmissions from *other potential sources of interference*.

Ideal for use in high-density transmit paths, the model 18663 provides excellent rejection of these other bands:

Maritime Radionavigation	3 - 3.1 GHz
Radar	3.1 - 3.45 GHz
WiMAX	3.4 - 3.8 GHz
X-band	7.25 - 8.4 GHz
Maritime & Aeronautical	
Radionavigation	9 - 11 GHz

- $\bullet \ \ \textit{Very low Insertion Loss} = \textit{Minimal Signal Degradation}.$
- Ideal for INSAT and other Extended C-band Applications.
- Easily bolt-on installation and no power supply required.



Specifications:

Passband: 4.5 - 4.8 GHz

Passband Loss: 0.2 dB Max Passband VSWR: 1.22:1 Max

Rejection: 80 dB Min from 1 - 3.9 GHz


20 dB Min from 3.9 - 4.3 GHz 70 dB Min from 5.4 - 5.85 GHz 80 dB Min from 5.85 - 12 GHz


Flanges: CPR229G

Dimensions: 6.36" x 3.88" x 2.75"

(162 mm x 98 mm x 70 mm)

Finish: Gloss White Lacquer





All MFC Products Designed and Manufactured in the USA



E-Mail: Sales@iktechcorp.com