



WAYFARER™ WFA120KA

1.2m Ka-Band Auto Fly-Away

The Norsat WAYFARER™ commercial 1.2m fly-away antenna is a fast deploying, easy-to-use, and compact SATCOM VSAT. This antenna is an excellent choice for commercial applications in various industries.

The WAYFARER 1.2m fly-away antenna offers excellent rugged and reliable satellite links for remote enterprise, energy, emergency, and media applications.

FEATURES

- Easy and intuitive LinkControl™ Interface
- Rugged and lightweight pedestal design
- Lightweight and durable 8 segment carbon fiber reflector
- Fast, simple, tool-free deployment
- Automatic 3-axis acquisition
- 2-case packing solution
- Wide range of Norsat BUC and LNB configurations
- Set up in 5 minutes



SPECIFICATIONS

ELECTRICAL

Reflector aperture	1.2m
Reflector material	Carbon fiber
Feed configuration	Center
Tx frequency	29.0 to 31.0 GHz
Rx frequency	18.7 to 21.2 GHz
Tx gain	46.4 dBi @ 29.0 GHz
Rx gain	43.3 dBi @ 18.7 GHz
Polarization	Circular
Cross polarization (On-Axis)	≥ 23.5 dB
Tx/Rx isolation (port isolation)	Tx ≥ 100 dB
Sidelobe	First sidelobe -14 dB
Azimuth range	± 200°
Elevation range	10° to 90°
Azimuth speed	0.1°/s to 3°/s
Elevation speed	0.1°/s to 3°/s
Polarization speed	0.1°/s to 1°/s
Feed interface	WR75
Power supply	AC110-230V 50/60Hz, rated 200W, 550W max

MECHANICAL

Ruggedized weatherproof case

Case 1	Pedestal assembly	Size: 84.5 cm (L) x 62 cm (W) x 49 cm (H); Weight: ≤30Kg
Case 2	Reflector / feed	Size: 84.5 cm (L) x 62 cm (W) x 49 cm (H); Weight: ≤22Kg

ENVIRONMENTAL

Wind load - operational	49 km/h
Wind load - survival	100 km/h
Operational Temperature	-30°C to +60°C
Storage Temperature	-50°C to +70°C
Humidity	0-95%
Water ingress	IP 65 (antenna only)

WAYFARER WFA120KA 1.2M KA-BAND AUTO FLY-AWAY ANTENNA

HOW TO ORDER

WFA120KA-NA

KA: Ka-Band

AC POWER PLUG

NA = North America (NEMA 5/15)

UK = UK (BS 1363)

EU = Europe (CEE 7/7)

IEC = IEC (60320 CIA)

ACCESSORY OPTIONS

BUC OPTIONS

BUC OPTIONS	BUC	BUC POWER SUPPLY	BUC M & C CABLE	BUC MOUNTING BRACKETS
12W	ELMTBKA012	PS300-AT1(NA/UK/EU/IEC)	CABLEM+C-AT10	WFA120KUMT-024
25W	ATOMBKA025	PS300-AT1(NA/UK/EU/IEC)	CABLEM+C-AT10	WFA120KUMT-024
50W	ATOMBKA050	PS600-AT1(NA/UK/EU/IEC)	CABLEM+C-AT10	WFA120KUMT-024

LNB OPTIONS

LNB	SERIES
LNB	9000 Series

IFL CABLE OPTIONS

IFL CABLE OPTIONS	NN-FF	NN-NN	FN-NN	FN-FF
IFL Cable (10m)	IFL-NN-FF-10	IFL-NN-NN-10	IFL-FN-NN-10	IFL-FN-FF-10

MODEM CABLE OPTION (For iDirect product only)

MOD-CABLE

INTEGRATION

WF-INT Assembly, function verification, and pointing test (standard product/RF packages only)